


ADVANCED FRAMING



**CHRIS PRICE
TECHNICAL SERVICES OFFICER
BIMOSE TRIBAL COUNCIL**

ADVANCED FRAMING OR OPTIMUM VALUE ENGINEERING

**IS A FRAMING SYSTEM THAT AIMS TO
REDUCE THE AMOUNT OF LUMBER TO
A BARE MINIMUM**

ADVANCED FRAMING

**WAS DEVELOPED IN THE 1960s AS A WAY
FOR BUILDERS TO REDUCE THEIR FRAMING
COSTS**

**IF YOU CAN SAVE ON LUMBER YOU CAN
SPEND MORE ON OTHER BUILDING
COMPONENTS OR LABOUR**

LESS WOOD MEANS MORE INSULATION

ADVANCED FRAMING

**LOWER LABOUR COSTS – ONCE YOU GET THE
HANG OF IT!!**

**REDUCED ENVIRONMENTAL COST
LESS WOOD = LESS TREES**

ADVANCED FRAMING

DESIGN WILL TAKE LONGER

TRAINING

**SOME SIDING CAN'T BE USED
WITH 24" O.C. FRAMING**


ADVANCED FRAMING

WARNING!!!!


**YOU MAY NOT WANT TO DIVE HEAD FIRST
INTO ALL OF THESE DETAILS**

WALL STUDS DIRECTLY BELOW EACH TRUSS

**TRUSSES @ 24" O.C.
WITH
STUDS @ 24" O.C.
STACKED FRAMING**




WALL STUDS AT 24" ON CENTER



**2"x4" WALL CAN
SUPPORT UP TO
ROOF + ATTIC**


**2"x6" WALL CAN
SUPPORT UP TO
ROOF + ATTIC +
FLOOR**

**SINGLE TOP PLATE
BUT BE CAREFULL!!!
94 1/8" STUDS**




**SINGLE TOP PLATE
BUT BE CAREFULL!!!**

+/- 2"




**SINGLE TOP PLATE
LAP JOINT AT LINTEL
OR**




SINGLE TOP PLATE SPLICE PLATES ARE REQUIRED

Top plate splice




WALL STUDS AT 24" ON CENTER




**FOR YOUR FIRST TRY
I WOULD HIGHLY
RECOMMEND
KEEPING A DOUBLE
TOP PLATE TO
SIMPLIFY A LOT OF
DETAILS**




**WINDOW OPTIONS
WITHIN EACH 24" CENTER
NO LINTELS NEEDED!!!**




CANNOT PUT OPENINGS IN ADJACENT CAVITIES!!!





WITHIN 2 CAVITIES
NO JACK STUDS WITH HANGERS!!
NO SILL CRIPPLES!!



LAYOUT WINDOWS AND DOORS SO THAT YOU GET 16" O.C. SPACING



HEADER HANGER




OPENING LINTELS



**SIZE EACH LINTEL FOR EACH OPENING
DON'T JUST USE 2-2"x10"**



SAME RULES CAN APPLY FOR DOORS




SO FAR WE HAVE DONE THIS!!




LET SAVE FROM FRAMING AT CORNERS

THREE-STUD CORNERS


INSULATED THREE-STUD CORNER (CALIFORNIA CORNER)




CONVENTIONAL CORNER





INSULATED THREE-STUD CORNER (INSIDE CORNER)




ALTERNATE INSULATED THREE-STUD CORNER (WITH DRYWALL CLIPS)



DRYWALL CLIP/STOP



NOW WHAT ABOUT INTERIOR PARTITIONS??




**DESIGN YOUR
PARTITIONS TO LINE
UP WITH AN
EXTERIOR STUD**

**USE A 1"x6" FOR A
DRYWALL NAILER**

NOW WHAT ABOUT INTERIOR PARTITIONS??

**USE 1"x4" @ 2' O.C.
FOR A DRYWALL
NAILER**



WHAT ARE OUR SHEATHING OPTIONS WITH STUDS AT 24" O.C.???

- **½" OSB**
- **½" EXT. PLYWOOD**
- **1-1/2" EXPANDED RIGID INSULATION**
- **1" EXTRUDED RIGID INSULATION**
- **NONE! YOU DON'T HAVE TO USE IT IF YOU WANT.**

WHAT ARE OUR SHEATHING OPTIONS WITH STUDS AT 24" O.C.???

POLYSTYRENE TYPE 1,2 EXPANDED




POLYSTYRENE TYPE 3,4 EXTRUDED



SO NO WOOD SHEATHING??

**THEN WE WILL NEED SOME
CROSS BRACING.**





RULES FOR CROSS BRACING

- **1"x4" AT 45° LET-IN FROM BOTTOM PLATE TO TOP PLATE**
- **2-2-1/2" NAILS EVERY STUD AND PLATE**
- **ONE EVERY WALL EVERY STOREY**
- **GENERAL GUIDE IS NOT TO HAVE A WALL UNBRACED FOR MORE THAN 24'**
- **THIS IS TO WORK IN COMBINATION WITH THE INTERIOR FINISH FOR LATERAL STRENGTH**

OTHER TYPES OF CROSS BRACING

DIAGONAL METAL STRAPPING



WHY CHOOSE RIGID INSULATION??

REDUCES THERMAL BRIDGING

**STRUCTURE HAS A HIGHER TEMPERATURE
IN THE WINTER**

**CAN PREVENT CONDENSATION ON THE
SHEATHING**

NEEDED R-VALUE


WHY NOT TO CHOOSE RIGID INSULATION??

COST


NEW TECHNIQUES AND TRAINING NEEDED

**DETAILS AROUND WINDOWS AND DOORS
ARE LABOUR INTENSIVE**

FOR UP TO 1" EXT. RIGID INSULATION



GREATER THAN 1" EXT. RIGID INSULATION



INSULATION TIPS

**USE A LITTLE FASTENERS AS POSSILBE
THE STRAPPING WILL BE DOING THE WORK**

USE THE LARGEST SHEETS POSSIBLE

USE AS LITTLE LAYERS AS POSSIBLE

HORIZONTAL VS. VERTICAL

MARK WHERE YOUR STUDS ARE AT EACH LAYER

STRAPPING



NEEDED FOR SIDING

1"x4" OR PLYWOOD

**IMPROVES AIR FLOW
BEHIND SIDING**

**PERFECT HOME FOR
BUG AND BATS**

FASTENING STRAPPING

AT 24" O.C.

Foam thickness	Fastener spacing (assuming vinyl siding)	Fastener spacing (assuming fiber-cement siding)	Fastener spacing (assuming stucco cladding)	Fastener spacing (assuming adhered manufactured stone veneer)
4 in. or less	24 in.	24 in.	12 in.	Don't do it
3 in. or less	24 in.	24 in.	16 in.	8 in.
2 in. or less	24 in.	24 in.	24 in.	12 in.
1 in. or less	24 in.	24 in.	24 in.	16 in.

FASTENING STRAPPING


STRAPPING AT 24" O.C.

Foam thickness	Fastener spacing (assuming vinyl siding)	Fastener spacing (assuming fiber-cement siding)	Fastener spacing (assuming stucco cladding)	Fastener spacing (assuming adhered manufactured stone veneer)
4 in. or less	24 in.	24 in.	12 in.	Don't do it
3 in. or less	24 in.	24 in.	16 in.	8 in.
2 in. or less	24 in.	24 in.	24 in.	12 in.
1 in. or less	24 in.	24 in.	24 in.	16 in.

FASTENING STRAPPING

STRUCTURAL WOOD SCREWS

NEED 1-1/2" INTO STRUCTURE




Deckfast

HeadLOK



**YELLOW
ZINC**

GRK



SIDING NAILING

KAYCAN:

VINYL = 16" O.C.

ENGINEERED WOOD = 16" O.C.

CANEXEL:

CED-R-VUE = 16" O.C.

RIDGEWOOD = 16" O.C.

ULTRAPLANK = 16" O.C.

SIDING NAILING

LP:

SMARTSIDE = 16" O.C.

PRECISION PANEL 190 = 24" O.C.

HARDIE CEMENT:

HARDIEPLANK = 24" O.C.

WINDOWS


INNIE VS. OUTIE



www.finehomebuilding.com




INNIE WINDOW



INNIE WINDOW



OUTTIE WINDOW



OUTIE WINDOW



OUTIE WINDOW



OUTIE WINDOW



OUTIE WINDOW

